



Trail Boss®
SAFETY DATA SHEET
June 2017

The following smokeless powders are distributed by Hodgdon Powder Company.

Trail Boss® **(EX-2012010854)**

1.4C EX Approval in bold parenthesis

Propellant Trail Boss

Thales (Thales Australia Limited)

Chemwatch Hazard Alert Code: 3

Chemwatch: 4638-27

Issue Date: 08/04/2016

Version No: 10.1.1.1

Print Date: 12/19/2016

Safety Data Sheet according to WHS and ADG requirements

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Propellant Trail Boss
Synonyms	Trail Boss AS25BP
Proper shipping name	POWDER, SMOKELESS
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions. Porous single-base smokeless powder or propellant for pistol ammunition.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Thales (Thales Australia Limited)	Thales (Thales Australia Limited)
Address	Private Bag 1 Mulwala NSW 2647 Australia	Bayly Street Mulwala NSW 2647 Australia
Telephone	Not Available	+61 3 5742 2200
Fax	Not Available	+61 3 5744 1873
Website	Not Available	Not Available
Email	Not Available	Not Available

Emergency telephone number


Association / Organisation	Not Available	Thales Australia Mulwala Facility
Emergency telephone numbers	Not Available	03 5742 2200
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification ^[1]	Explosive Division 1.3, Reproductive Toxicity Category 1B, Acute Aquatic Hazard Category 2, Chronic Aquatic Hazard Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	
--------------------	---

SIGNAL WORD	DANGER
-------------	--------

Hazard statement(s)

H203	Explosive; fire, blast or projection hazard.
H360	May damage fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P230	Keep wetted with phlegmatizer.
P250	Do not subject to grinding/shock/sources of friction.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/attention.
P370+P380	In case of fire: Evacuate area.
P372	Explosion risk in case of fire.
P373	DO NOT fight fire when fire reaches explosives.

Precautionary statement(s) Storage

P405	Store locked up.
P401	Store according to local regulations for explosives.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
-------------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
9004-70-0	>70	<u>nitrocellulose</u>
84-74-2	<15	<u>dibutyl phthalate</u>
122-39-4	<2	<u>diphenylamine</u>
Not Available	<5	inorganic potassium compounds
Not Available	<1	additives non-hazardous

SECTION 4 FIRST AID MEASURES**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.

Ingestion	<ul style="list-style-type: none"> ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.
------------------	--

Indication of any immediate medical attention and special treatment needed

Symptoms of vasodilation and reflex tachycardia may present following organic nitrate overdose; most organic nitrates are extensively metabolised by hydrolysis to inorganic nitrites. Organic nitrates and nitrites are readily absorbed through the skin, lungs, mucosa and gastro-intestinal tract. Delayed pulmonary oedema may result following exposure to nitrous oxides formed on thermal decomposition of the propellant.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

DANGER: Deliver media remotely.

- ▶ For minor fires: Flooding quantities only.
- ▶ For large fires: **Do not attempt to extinguish.**

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<p>WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!</p> <ul style="list-style-type: none"> ▶ Evacuate all personnel and move upwind. ▶ Prevent re-entry. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be explosively reactive, detonate and release much heat. <p>For Division 1.3 Explosives Evacuation is required in case of Emergency. For quantities of up to:</p> <ul style="list-style-type: none"> ▶ 1000 kg, the evacuation distance is 100 metres ▶ 5000 kg, the evacuation distance is 150 metres ▶ 20000 kg, the evacuation distance is 200 metres ▶ 40000 kg, the evacuation distance is 250 meters
Fire/Explosion Hazard	<p>Division 1.3 Substances, mixtures and articles which have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but not a mass explosion hazard (a mass explosion is one which affects almost the entire quantity present virtually instantaneously):</p> <p>(i) combustion of which gives rise to considerable radiant heat; or (ii) which burn one after another, producing minor blast or projection effects or both</p> <p>Explosives are defined as substances which are capable by chemical reaction of producing gas at such a temperature and pressure and at such speed as to cause damage to the surroundings. Pyrotechnic substances are included even when they do not evolve gases</p> <p>Compatibility Group C explosives are propellant explosive substances or other deflagrating explosive substances or article containing such explosive substances.</p> <p>WARNING: EXPLOSION HAZARD!</p> <ul style="list-style-type: none"> ▶ Combustible. ▶ Detonation may occur from heavy impact or excessive heating. ▶ Mixing with incompatible chemicals may cause expansion, decomposition or detonation. ▶ Heat affected containers remain hazardous. <p>Combustion products include: carbon monoxide (CO) carbon dioxide (CO₂) nitrogen oxides (NO_x) other pyrolysis products typical of burning organic material.</p>
HAZCHEM	E

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<p>Environmental hazard - contain spillage. WARNING!: EXPLOSIVE. BLAST and/or PROJECTION and/or FIRE HAZARD</p> <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid inhalation of the material and avoid contact with eyes and skin. ▶ Wear impervious gloves and safety glasses.
Major Spills	<p>Environmental hazard - contain spillage. WARNING!: EXPLOSIVE.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. <p>In the case of transport accident notify the State Police, State Explosives Inspector and the Manufacturer, ADI Mulwala Facility. Collect recoverable packages and segregate from loose, spilled material.</p>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<p> </p> <ul style="list-style-type: none"> ▶ Handle gently. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Avoid all personal contact, including inhalation. ▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions) ▶ Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. ▶ Establish good housekeeping practices. ▶ Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. <p>Avoid prolonged storage (longer than shelf-life) storage temperatures above 38 deg C (100 F). Store in tightly closed containers in a properly vented storage area away from heat, sparks, open flame, strong oxidisers, radiation and other initiators.</p> <p>Prevent contamination by foreign materials. Prevent moisture contact.</p>
Other information	<p> </p> <ul style="list-style-type: none"> ▶ Store cases in a well ventilated magazine licenced for the appropriate Class, Division and Compatibility Group. ▶ Rotate stock to prevent ageing. Use on FIFO (first in-first out) basis. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. <p>Store cases in a well ventilated magazine licensed for IMCO Class 1.3C Explosives. NOTE: If deterioration of the explosive occurs or large quantities of explosive need to be destroyed notify the Manager, ADI Mulwala Facility or State Explosives Department.</p>

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ All packaging for Class 1 Goods shall be in accordance with the requirements of the relevant Code for the transport of Dangerous Goods. ▶ Class 1 is unique in that the type of packaging used frequently has a very decisive effect on the hazard and therefore on the assignment to a particular division <p>Packaging for explosive substances shall meet the test requirements for Packaging Group II. Explosives Code Packing Instruction P114(b) or 114(b) General packaging provisions of 4.1.1, 4.1.3 and special provision 4.1.5 are to be met. For UN 0160, 0161 - If outer packaging is drum then inner packaging is not required. For UN 0160, 0161 - If outer packaging is 1A2 or 1B2 metal drums then drum construction shall be such that risk of explosion, by reason of increase by internal pressure from internal or external causes, is prevented. For UN 0077, 0132, 0234, 0235, 0236, packagings are to be lead free, otherwise: Inner Packagings: Bags: Paper Kraft, Plastics, Textiles - sift proof, Woven Plastic - sift proof Receptacles: Fibreboard, Metal, Paper, Plastic, Woven Plastic - sift proof Intermediate Packagings: Not necessary Outer Packagings: Boxes: Natural Wood (4C1), Natural Wood -sift proof (4C2), Plywood (4D), Reconstituted Wood (4F), Fibreboard (4G) Drums: Steel, Removable Head (1A2), Aluminium, removable head (1B2), Plywood (1D), Fibre (1G), Plastic, removable head (1H2)</p>
---------------------------	---

Storage incompatibility

- ▶ Avoid strong acids, bases.
 - ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials.
 - ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.
 - ▶ Avoid reaction with oxidising agents
- Do NOT allow to dry.



X X X X X X X

X — Must not be stored together

0 — May be stored together with specific precautions

+ — May be stored together

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	nitrocellulose	Fume (thermally generated) (respirable dust)	2 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	dibutyl phthalate	Dibutyl phthalate	5 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	diphenylamine	Diphenylamine	10 mg/m ³	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
dibutyl phthalate	Dibutyl phthalate	15 mg/m ³	84 mg/m ³	9300 mg/m ³
diphenylamine	Diphenylamine	30 mg/m ³	180 mg/m ³	220 mg/m ³

Ingredient	Original IDLH	Revised IDLH
nitrocellulose	Not Available	Not Available
dibutyl phthalate	9,300 mg/m ³	4,000 mg/m ³
diphenylamine	Not Available	Not Available
inorganic potassium compounds	Not Available	Not Available
additives non-hazardous	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls for explosive substances are designed to reduce or eliminate fragmentation and/or blast effects either by suppression of the source of detonation or by protection at the exposed location, or both. Barricades, shields, contained detonation chambers, and "zero quantity-distance (Q-D)" magazines are examples of engineering controls.</p> <p>Engineering controls are designed and tested in a rigorous fashion. The construction of the engineering control must be carefully duplicated in field applications to assure it will function properly.</p> <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
Personal protection	

Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p> <ul style="list-style-type: none"> -Non-sparking or conductive footwear essential. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn.
Body protection	See Other protection below
Other protection	<p> </p> <p>For handling explosives or explosive compositions:</p> <ul style="list-style-type: none"> ▶ Wear close-fitting flame-protection treated clothing closed at the neck and sleeves. ▶ Cotton underwear, socks and conductive shoes are recommended to avoid human static discharge. <p>Manufacture may require:</p> <ul style="list-style-type: none"> ▶ Non-static flame retardant treated clothing ▶ Access to deluge Safety shower ▶ Barrier cream. <p>Manufacture may require: Non-static clean room clothing.</p>
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Propellant Trail Boss

Material	CPI
BUTYL	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
PE/EVAL/PE	C
PVA	C
VITON	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A P1 Air-line*	- -	A PAPR-P1 -
up to 50 x ES	Air-line**	A P2	A PAPR-P2
up to 100 x ES	-	A P3 Air-line*	-
100+ x ES	-	Air-line**	A PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ **Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.**
- ▶ **The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).**
- ▶ **Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.**
- ▶ **Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.**
- ▶ **Use approved positive flow mask if significant quantities of dust**

- ▶ becomes airborne.
- ▶ Try to avoid creating dust conditions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Small grey, green-grey disc shaped granules; does not mix with water. WARNING: SEVERE EXPLOSION HAZARD. Detonation may occur from heavy impact or excessive heating. Avoid all contact with other chemicals.		
Physical state	Divided Solid	Relative density (Water = 1)	Approx. 0.6
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	170
pH (as supplied)	Not Applicable	Decomposition temperature	Explosive.
Melting point / freezing point (°C)	>170 decomposes	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Non Volatile	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Negligible
Vapour pressure (kPa)	Negligible	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Presence of shock and friction ▶ Presence of heat source and ignition source ▶ Product is considered stable under normal handling conditions. ▶ Stable under normal storage conditions. ▶ Hazardous polymerization will not occur. ▶ Avoid contact with other explosives, pyrotechnics, solvents, adhesives, paints, cleaners and unauthorized metals, plastics, packing equipment and materials. ▶ Avoid contamination with acids, alkalis, reducing agents, amines and phosphorus.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper
----------------	--

	screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	Skin contact with the material may be harmful; systemic effects may result following absorption. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.
Chronic	Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. Long term exposure to high dust concentrations may cause changes in lung function i.e. pneumoconiosis, caused by particles less than 0.5 micron penetrating and remaining in the lung.

Propellant Trail Boss	TOXICITY	IRRITATION
	Not Available	Not Available
nitrocellulose	TOXICITY	IRRITATION
	Oral (rat) LD50: >5000 mg/kg ^[2]	Not Available
dibutyl phthalate	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >21000 mg/kg ^[2]	Not Available
	Inhalation (mouse) LC50: 25 mg/L/2hr ^[2]	
	Oral (rat) LD50: 6279 mg/kg ^[1]	
diphenylamine	TOXICITY	IRRITATION
	Oral (hamster) LD50: ca.600 mg/kg ^[1]	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

NITROCELLULOSE	No significant acute toxicological data identified in literature search.	
DIBUTYL PHTHALATE	<p>For dibutyl phthalate (DBP):</p> <p>In studies on rats, DBP is absorbed through the skin, although in <i>in vitro</i> studies human skin has been found to be less permeable than rat skin to this compound. Studies in laboratory animals indicate that DBP is rapidly absorbed from the gastrointestinal tract, distributed primarily to the liver and kidneys of rats and excreted in urine as metabolites following oral or intravenous administration. Following inhalation, it was consistently detected at low concentrations in the brain. Available data indicate that in rats, following ingestion, DBP is metabolised by nonspecific esterases mainly in the small intestine to yield mono- <i>n</i>-butyl phthalate (MBP) with limited subsequent biochemical oxidation of the alkyl side chain of MBP. The material may produce peroxisome proliferation. Peroxisomes are single, membrane limited organelles in the cytoplasm that are found in the cells of animals, plants, fungi, and protozoa.</p> <p>Available data indicate that phthalate esters are minimally toxic by swallowing, inhalation and skin contact. Repeated exposure may result in weight gain, liver enlargement and induction of liver enzymes. They may also cause shrinking of the testicles and other structural malformations. They may reduce male and female fertility and number of live births, according to animal testing.</p>	
DIPHENYLAMINE	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.</p> <p>Diphenylamine and all its substituted derivatives show slight to moderate acute toxicity. Overall, it is not considered to cause mutations or genetic toxicity. In animal testing, higher concentrations appear to reduce the number of viable offspring.</p> <p>ADI: 0.02 mg/kg/day NOEL: 1.5 mg/kg/day</p>	
Acute Toxicity	<input type="radio"/>	Carcinogenicity
Skin Irritation/Corrosion	<input type="radio"/>	Reproductivity
		<input checked="" type="checkbox"/>

Serious Eye Damage/Irritation	☉	STOT - Single Exposure	☉
Respiratory or Skin sensitisation	☉	STOT - Repeated Exposure	☉
Mutagenicity	☉	Aspiration Hazard	☉

Legend: ✗ – Data available but does not fill the criteria for classification

✔ – Data required to make classification available

☉ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
nitrocellulose	EC50	96	Algae or other aquatic plants	579mg/L	4
dibutyl phthalate	LC50	96	Fish	0.35mg/L	4
dibutyl phthalate	EC50	48	Crustacea	2.99mg/L	4
dibutyl phthalate	EC50	96	Algae or other aquatic plants	0.0034mg/L	4
dibutyl phthalate	BCF	24	Algae or other aquatic plants	10mg/L	4
dibutyl phthalate	EC0	240	Crustacea	=0.1mg/L	1
dibutyl phthalate	NOEC	144	Fish	0.025mg/L	4
diphenylamine	LC50	96	Fish	3.287mg/L	3
diphenylamine	EC50	48	Crustacea	0.31mg/L	4
diphenylamine	EC50	72	Algae or other aquatic plants	0.048mg/L	1
diphenylamine	BCF	768	Fish	0.0437mg/L	4
diphenylamine	EC50	384	Crustacea	0.812mg/L	3
diphenylamine	NOEC	504	Crustacea	0.16mg/L	1

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
dibutyl phthalate	LOW (Half-life = 23 days)	LOW (Half-life = 3.08 days)
diphenylamine	LOW (Half-life = 56 days)	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
dibutyl phthalate	LOW (BCF = 176)
diphenylamine	LOW (BCF = 253)

Mobility in soil

Ingredient	Mobility
dibutyl phthalate	LOW (KOC = 1460)
diphenylamine	LOW (KOC = 1887)

SECTION 13 DISPOSAL CONSIDERATIONS



Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. Explosives must not be thrown away, buried, discarded or placed with garbage.
------------------------------	--

- ▶ This material may be disposed of by burning or detonation but the operation must be performed under the control of a person competent in the destruction of explosives.
- Disposal by detonation:
- ▶ The explosives to be destroyed must be placed in direct contact with fresh priming charge in a hole which is at least 0.6 metre deep and then adequately stemmed.
 - ▶ Explosives must not be thrown away, buried, discarded or placed with garbage.
 - ▶ Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified.
 - ▶ This material may be disposed of by burning or detonation but the operation may only be performed under the control of a person trained in the safe destruction of explosives.

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	
HAZCHEM	E

Land transport (ADG)

UN number	0161
UN proper shipping name	POWDER, SMOKELESS
Transport hazard class(es)	Class : 1.3C Subrisk : Not Applicable
Packing group	Not Applicable
Environmental hazard	Not Applicable
Special precautions for user	Special provisions : Not Applicable Limited quantity : 0

Air transport (ICAO-IATA / DGR)

UN number	0161
UN proper shipping name	Powder, smokeless
Transport hazard class(es)	ICAO/IATA Class : 1.3C ICAO / IATA Subrisk : Not Applicable ERG Code : 1L
Packing group	Not Applicable
Environmental hazard	Not Applicable
Special precautions for user	Special provisions : Not Applicable Cargo Only Packing Instructions : Forbidden Cargo Only Maximum Qty / Pack : Forbidden Passenger and Cargo Packing Instructions : Forbidden Passenger and Cargo Maximum Qty / Pack : Forbidden Passenger and Cargo Limited Quantity Packing Instructions : Forbidden Passenger and Cargo Limited Maximum Qty / Pack : Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	0161
-----------	------

UN proper shipping name	POWDER, SMOKELESS	
Transport hazard class(es)	IMDG Class	1.3C
	IMDG Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-B, S-Y
	Special provisions	Not Applicable
	Limited Quantities	0

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

NITROCELLULOSE(9004-70-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

DIBUTYL PHTHALATE(84-74-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

DIPHENYLAMINE(122-39-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (nitrocellulose; diphenylamine; dibutyl phthalate)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	N (nitrocellulose)
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

Notes

When the propellant is packed as in packaging UN4GY12.5/S/**/AUS/ABBE 30818 it is suitable for air transport as follows:

Air Transport IATA

ICAO/IATA Class: 1.4C ICAO/IATA Subrisk: None

UN/ID Number 0509 Packing Group:-

Special Provisions: none

Cargo Only

Packing Instructions: 114 Maximum Qty/Pack: 5kg

Passenger and Cargo

Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

Passenger and Cargo

Limited Quantity

Packing Instructions: Forbidden Maximum Qty/Pack: Forbidden

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.